

EXTREME CRANE LUBE

Special Instructions for Safe and Efficient Use

- **Caution during application:** Exercise caution when handling this product. Extreme Crane Lube is flammable during spraying. Ensure that there is no smoking, open flames, or sparks in the vicinity where the product is being applied. **It should be noted that the flammability diminishes after about 5 minutes from being sprayed.** When not in use, store the product away from direct sunlight or, if available and required, within suitable Flammable Safe Cabinets. The product is not susceptible to freezing; for more details, please consult the Safety Data Sheet (SDS).
- **Safety Gear:** Ensure the use of appropriate protective gear as necessary. When required, use gloves, face mask, safety glasses, & designated clothing. Have proper ventilation if spraying indoors.
- **Shake Before Use:** Before applying Extreme Crane Lube, vigorously shake the container for about 30 seconds. This step ensures proper blending of the product for optimal performance.
- **Select an Appropriate Sprayer:** Transfer the Extreme Crane Lube into your chosen pump sprayer applicator. Use only Airless Sprayers when spraying. For specific recommendations on pump sprayers, please reach out to your local Extreme Crane Lube dealer or view the [recommended sprayers page](#).
- **Optimal Pressure Setting:** Pump up the sprayer to your desired pressure level. Maintaining good pressure is crucial as it facilitates the atomization of the product, resulting in an improved spray pattern and comprehensive coverage.
- **Single Coat Application:** Extreme Crane Lube is designed for a minimum of one coat per application. This minimizes material waste and results with less scrape off. More than one coat can be applied. If you observe any sagging or running, it indicates an excessive application.
- **Check Before Scoping In:** Let applied product setup and get tacky before scoping in or operating equipment. **Check that the applied product is sticky before scoping inward.** *It can take 5-10 minutes to setup and get sticky depending on how heavy the product was applied.* Dries faster in warmer temperatures.
- **Efficient Clean-Up:** After use, pour any remaining product back into its original container. Alternatively, you may choose to leave the contents in the sprayer. Crucially, release all pressure within the sprayer to prevent accidental product discharge. Clean the sprayer nozzles and inside the sprayer when they become clogged or have residue build up. Some residue can form on the insides of sprayers after long periods of use. We recommend using a degreaser of choice to clean any residue inside the sprayers, only when problematic.

For any inquiries or concerns, please do not hesitate to contact us at Extreme Crane Lube. Visit our website for more information and support. Your safety and satisfaction are our top priorities.